



- **COMPATIBLE FORK SIZES** - 150mm to 203mm
- **SEATPOST** – 30.9mm
- **FRONT DERAILLEUR** – 34.9mm Top Swing/Top Pull (or Saint 34.9mm Top Swing/Top Pull using 150 x 12mm dropouts and appropriate 56-57mm chainline cranks)
- **BB SHELL** – 73mm, ISCG-05
- **REAR WHEEL** – 135 x 10mm or 150 x 12mm
- **RECOMMENDED REAR MAX TIRE SIZE** - 2.5"
- **DISC BRAKE ROTORS** - 203mm max.
- **HEADTUBE** - 1-5"

--	--	--	--	--



RIDER WEIGHT	PRESSURE MAIN	BOOST VALVE	PRO PEDAL	BOTTOM OUT	REBOUND	SHOCK SAG
100 lbs (45.5 kg)	140 psi (9.65 bar)	125 psi	10 Ret	1.5 Ret	11 Ret	15-17 mm
120 lbs (54.4 kg)	160 psi (11 bar)	125 psi	10 Ret	1.5 Ret	10 Ret	15-17 mm
140 lbs (63.5 kg)	180 psi (12.4 bar)	125 psi	10 Ret	1.5 Ret	10 Ret	15-17 mm
160 lbs (72.6 kg)	200 psi (13.8 bar)	125 psi	10 Ret	1.5 Ret	9 Ret	15-17 mm
180 lbs (81.8 kg)	220 psi (15.2 bar)	125 psi	10 Ret	1.5 Ret	9 Ret	15-20 mm
200 lbs (90.7 kg)	240 psi (16.5 bar)	125 psi	10 Ret	1.5 Ret	8 Ret	15-20 mm
220 lbs (99.8 kg)	260 psi (17.9 bar)	125 psi	10 Ret	1.5 Ret	8 Ret	15-20 mm
240 lbs (108.8 kg)	280 psi (19.3 bar)	125 psi	10 Ret	1.5 Ret	7 Ret	15-20 mm

FOX DHX 5.0 AIR

RIDER WEIGHT	SPRING RATE	PRELOAD	SHOCK SAG
100 lbs (45.5 kg)	250	1 Turn	15-18 mm
120 lbs (54.4 kg)	300	1 Turn	15-18 mm
140 lbs (63.5 kg)	350	1 Turn	15-18 mm
160 lbs (72.6 kg)	400	1 Turn	15-18 mm
180 lbs (81.8 kg)	450	1 Turn	15-18 mm
200 lbs (90.7 kg)	500	1 Turn	15-18 mm
220 lbs (99.8 kg)	550	1 Turn	15-18 mm
240 lbs (108.8 kg)	600	1 Turn	15-18 mm

FOX VANILLA RC

Ret = The number of clicks out from fully closed position. Rebound setting is dependent upon shock pressure and rider preference. Please refer to your specific component manual, and feel free to experiment.